


Those Over-Grown Patches Owe You an Income — Clean and Break them with the Italian Brush Hoe

It eats Hard-Baked Soil,
Gravel, Brush, Roots,
or Sod, with



Its Wide, Weighted
Steel Blade and Smooth
White Ash Axe Handle.
You will find its TEMPER TRUE

for
Breaking-Grading-Cultivating.
YOUR DEALER SELLS IT
Ask Him for TRUE TEMPER

Always First in the Field

W. E. HEENEY
Funeral Director

All Calls Promptly Answered

Day or Night

Lady Assistant if Desired

Motor or Horse service.

From 18 to 20 Caskets Carried in Stock.

Telephone No. 24

Farmington, Mich.

When the housewife commences to think
of meal time and its preparation
she invariably thinks of

SCHROEDER
who always carries the best of Meats,
Lard, etc. Try it once
and you will too

Phone No. 5 Farmington

Established 1850 4,600 Students
Sixty-sixth Year
BUSINESS SHORTHAND COMMERCIAL TEACHING
D. B. U. Graduates always in demand for best positions
Send for catalogue
DETROIT BUSINESS UNIVERSITY
61-63-65-67-69 West Grand River Ave.
Detroit, Mich. B. W. McMANUS, Registrar

WELDING

When you are coming to town throw
into your rig those BROKEN CAST-
INGS, CAST IRON, STEEL, BRASS,
COPPER or ALUMINUM. Call at

The Park Garage

and we will demonstrate the possibility
of making them just as

Good as New

with the new process OXY-ACETY.

LENE WELDING

Don't forget, we refund your money on all castings
that do not hold.

CARL ELY, Prop'r Farmington

The Farmington Enterprise

W. E. Lord, Editor

Published Friday of each Week and en-
tered at the postoffice at Farmington, Mich., as second
class mail matter.

\$1.00 per year, in advance

Devoted to the upbuilding of Farmington
and Oakland County.

A shiftless man is always boasting
of what he would do if he had
the money...

We don't know whether a dollar
goes as far as it used to, but it
certainly goes faster.

Some people are willing to be
good if they are paid for it, and
others are good for nothing.

When it comes to Mexico Mr.
Bryan seems inclined to admit that
an Olive Branch has its limitations.

Many men in small towns have
many minds and naturally they
think differently on matters affect-
ing a town. A good plan is not to
be afraid of the cars. Whatever
benefits a community must of ne-
cessity benefit all the people. This
is an age of competition and if we
are not willing to compete with the
outside world why then are we
going to drag along. The small
town merchant should be able to
outsell the city merchant and he
does in a great majority of cases,
because he has lighter operating
expenses. It is the people of the
town that make it good or bad
every time.

In this age of invention and com-
petition our country people are
relaxing into their Ford cars, talk-
ing by telephone and reading by
electric light, and with these
changes the country newspaper
also, that companion of the fireside,
has taken a step forward. We are
getting education through the moving
pictures and the phonograph,
and state universities are multiply-
ing like the sands of the sea. In
these surroundings the country
newspaper has naturally changed
its face. The number of small and
insignificant sheets has become
fewer. The paper of the old days
was supported through charity.
The old editor used a more trea-
chary pen, but the good old times
of bontide have passed away, and
the old editors have gone to glory,
some of them carrying more buck
shot for ballast than they needed.
The publishing of a country paper
today is a business proposition, and
must be run on business principles,
or "go to the wall." Their stock
in trade is their advertising space,
for which the editor must receive
due compensation if he expects to
succeed.

Obituaries

Mrs. Olive A Clark died Fri-
day, 16, 1916 in Honolulu, at the
home of her son, Dr. F. E. Clark.

Mrs. Clark was born September
19th, 1841 in Rush, Monroe County,
N. Y. She was the oldest daughter
of Joseph H. P. and Maria A. Rose,
who had a family of twelve
children, five sons and seven daugh-
ters. All of the sons and three of
the daughters have gone home. The
late Mrs. L. N. Moon, whose
husband is a member of the De-
troit Conference, was one of the
sisters. Mrs. Chapin and Mrs.
Riley, of Honolulu, and Mrs.
Flicker and Mrs. Andrews, of Los
Angeles, are the four sisters re-
maining on earth.

Mr. Rose moved to Macomb
county, Michigan, when Olive was
six years old. In 1850 she was
married to Francis Drake Clark, of
Batavia, N. Y., and for more than
thirty years they lived in, or near
the Village of Farmington. About
twenty-three years ago, Mr. Clark
sold most of his property in Farm-
ington, and bought a home in Detroit,
where he died fourteen
years ago. Mrs. Clark went to
Honolulu to live with her son,
who had made her declining years
the brightest of her life.

She was a member of the First
M. E. church of Honolulu, and
although she has been partially
blind for several years her seat in
church on Sunday mornings, was
well known.

She had the happy
faculty of forming warm friend-
ships, and as her life here was
free from most persons, from
dense care, she enjoyed them
to the utmost. Her remains were
cremated, and her ashes will be

taken to Farmington in the near
future, to be buried by her husband
and two daughters.

John M. Grace, one-half mile
north and one-half east of Hold
No. 4, Clarenceville, will hold an
auction at his farm home on Sat-
urday, April 15th, when he will
sell without reserve his stock and
farm tools. John Wedow, au-
ctioneer.

J. J. Miller will sell at Public
Auction, on the premises 3 miles
east of Farmington Village or
three-eighths of a mile north of
Grand River, near the Switzer
road, on what is known as the
Webberish farm, on Friday, April
14th, his stock and farm tools.
Auctioneer, John Wedow.

Probate Order

STATE OF MICHIGAN — In The
probate court of Oakland
County, of said court, held at the
probate office in the city of Pontiac, in
said county, on the First day of April,
A. D. 1916.

Present, Hon. Kleber P. Rockwell,
Judge of Probate.

In the matter of the estate of

Anna Westfall,

John Landau, administrator of said
estate, having filed in said court a petition
and a copy of the will, and a statement and a de-
claration of his financial account, determining the
heirs-at-law of said deceased, dis-
tributing the assets of said estate, and dis-
charging said administrator. It is or-
dered that the

Twenty-ninth day of April,

A. D. 1916 at eight o'clock in the fore-
noon, at said probate office, he is and
hereby appointed for hearing said peti-
tion;

It is further ordered, That public
notice be given by publication in the publication
of a copy of this order, once each week for
three successive weeks previous to

the day of hearing, in the Farmington

Enterprise, a newspaper printed and cir-
culated in said county.

KLEBER P. ROCKWELL,
Judge of Probate.

JUNIOR A. FREDENBURG,
Probate Clerk.

AN ORDINANCE ESTABLISHING
SIDEWALKS IN THE VILLAGE OF
FARMINGTON.

The Village of Farmington ordains

Section I. That a sidewalk from
four to five feet is hereby established
on both sides of all the streets in the
Village of Farmington.

Section II. Said sidewalk is to be
constructed of such material as
shall be approved by the Village
Council, conditioned for the faithful
and safe use of the public, and
shall be at least four inches in
width, and be made of such
material as shall be approved by
the Village Council.

Made and passed by the Village of
Farmington this first day of July, A. D. 1916.

T. H. McGEE,
President.

FRANK N. STEELE,
Clerk.

AN ORDINANCE relating to the Con-
struction of Cement Sidewalks and Es-
tablishing the Construction and Es-
tablishment of Sidewalks.

The Village of Farmington ordains

Section I. Every builder of cement
sidewalks in said Village shall before
the completion of his sidewalk, or
such walk execute and file with the
Clerk of said Village a bond in such
amount, with such surety or sureties as
shall be approved by the Village
Council, conditioned for the faithful
and safe use of the public, and
shall be at least four inches in
width, and be made of such
material as shall be approved by
the Village Council.

Section II. All sidewalks and cross-
walks are to be constructed in said
Village shall be constructed in accord-
ance with the following specifications
and requirements:

Grading.

(1) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(2) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(3) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(4) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(5) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(6) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(7) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(8) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(9) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(10) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(11) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(12) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(13) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(14) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(15) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(16) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(17) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(18) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(19) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(20) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(21) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(22) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(23) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(24) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(25) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(26) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(27) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(28) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(29) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(30) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(31) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(32) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(33) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(34) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(35) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(36) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(37) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(38) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(39) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(40) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(41) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(42) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(43) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(44) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(45) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(46) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(47) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(48) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(49) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(50) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(51) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(52) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(53) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(54) The earth shall be excavated
for the width of three feet on
each side greater than the width of the
sidewalk to be laid and to a uniform
depth of four inches below the top
of the walk when laid; in clay or
heavy soils, excavations shall be to a
depth of six inches below the top of
the walk.

(55) The earth shall be