SLATE-FLAGSTONE
CARE OF NEW SLATE
FLOORS:
1. Be sure loose dirt and debris is removed.
2. Scrub slate with mild soluincommunication of muriatic acid. This will

2. Scrub slate with mild solu-tion of muriatic acid. This will remove excess mortar. Rinse thoroughly with clear water. Allow to dry. 3. Apply sealer making sure that the surface is evenly coated. Allow 2 hours for drying. 4. Apply a thin coat of slate and flagstone paste wax. 5. Buff thoroughly! Note: If slate is outside, apply 2 coats of sealer. Do not apply any wax on outside areas.

REGULAR CARE OF SLATE AND FLAGSTONE: •

Clean flagstone with solution
 floor cleaner. Use scrub
 brush. Rinse and allow to dry
 thoroughly.

brush. Rinse and allow to dry thoroughly.

2. Apply 2 costs of sealer. Allow 2 hours drying time between costs.

3. Apply a thin cost of slate and flagstone paste wax. Buff. so the cost of the state of lagstone it must be removed with instant wax stripper. Then follow regular care directions 2 and 3.

Check These Tips Before Refinishing Your Floor

FLOOR FINISHING AND MAINTENANCE TO THE Pure viryl is the most durable of the relative to the relative that the relative

or dirt and requires minimum care. Vinyl abbestos contains moisture-resistant asbestos and is somewhat less exper-sistant somewhat less exper-sistant abbestos water...allow floor to dry. A pply very thin coat of liq-direct properties of the contained of the NEW FLOOR CARE: For the first two weeks dry isher.

A HOUSE FULL OF FURNITURE FOUR-PIECE BEDROOM SET E button-free innerspring and matchin g mattess (10-yr guarantee) *TWO (FIVE-PIECE DINETTE SET \$365 PLAN DELIVERY

WAYNE HOME OUTFITTERS

mop only so that adhesives have proper time to dry. Then, follow these steps: FLOORS:

FLOORS:
Vinyl will not resist yellowing or discoloring with age due to use of any low quality floorpended, follow these steps:
1. Apply wax stripper. For excessive discoloration agitate vinit fine steet wool.
2. Let stand 3 to 5 minutes. Then agitate with floor machine and steet wool or synthesis pad. Remove., finish throughly, and and to liquid wax. Allow to dry. (Two thin coals are better than one heavy coât of wax.)

RUBBER TILE and
ASPHALT TILE
Rubber tile flooring is
widely used in new homes
where traditional linoleum and
hardwood used to appear, is
more resilient than convential
linoleum. Asphalt tile contains
moisture resilient asbeatos and
is the least expensive composition flooring.

NEW FLOOR CARE: For the first two weeks dry mop only so that adhesives have proper time to dry... Then follow these steps:



Sweep or dry mop entire floor area removing all surface dirt.
 Mop floor with floor cleaner solution.
 Rinse thoroughly with clear water. allow floor to dry.
 Apply very thin coat of liquid wax... allow to dry.
 Buff with electric floor polither.

isher REJUVENATING OLD

REJUVENATING OLD FLOORS:
Rubber tile and asphalt tile are resistant to most household liquids as well as denting. They will not, however, resist discoloration or yellowing caused by so globor will be a solid to the solid property of the solid

4. Buff with an electric floor polisher.

LINOLEUM

Linoleum has been used improperly to describe most floor coverings used in kitchens and bathrooms. This see which is made by rolling or pressing on to canvas or buriapa a large combination of gums, linseed oil, cork dust. wood, flour, and pigments.

NEW FLOOR CARE: For the first ten days dry mog, floors only. Do not use water so that aftesives have proper time to dry. Trôn, follow thees esteps:

1. Sweep or dry mog entire

2. Mop floor with Hoor cleaner solution.
3. Rinse thoroughly with clear water...allow floor to dry.
4. Apply thick coat of clear paste wax. Allow to dry.
5. Buff with electric floor polisher.

5. Buff with electric floor polisher.

REJUVENATING OLD

FLOORS:
Inderior liquid waxes cause a build-up of discoloration. If linoleum is discoloratio.

1. Use wax stripper.

2. Let stand 3 to 5 minutes. Then agitate with floor machine and steel wool of synthesis pad. Remove. .rinse thoroughly. .allow floor to dry.

3. Apply thin coat of clear paste wax. . (For extremely excellent results it is recommended an initial coat be clear paste wax. .e. at as base to a second coat of liquid wax.)

4. Buff with an electric floor polisher.

HARDWOOD FLOORS
NEW FLOOR CARE:
After a new floor is installed it is sanded, varnished and usually coated with a thin wax. This wax will not last for long. For professional floor-care use a solvent-base wax.

Dust mop all particles from surface.

2. Apply clear paste wax using fine steel wool or soft cloth.
3. Buff with an electric pol-

isher.
REJUVENATING WORN
FLOORS:
For old hardwood floors that
have become worn in spots
due to heavy traffic, use Indian sand. In the heavy traffic
lanes where the floor sealer
has worn away, it is not necesgary to sand and refinish en-

tire floor. Use the following method:

1. Clean floors with wood cleaner, using steel wool in extremely soiled areas.

2. Wipe dry with soft cloth...let floor dry at least one hour.

hour.
3. Apply Indian sand with fine steel wool...let dry 5 to 10 minutes. 4. Buff with an electric floor

polisher. Note: For extremely worn areas two coats may be neces-

CORK

One of the most luxurious floor coverings, cork is generally installed in areas not subject to hard wear. It does not resist dirt, water or grease as well as other floors, but is resi-lient and quiet. NEW FLOOR CARE:

NEW FLOOR CARE:

Omain the first ten days of installation, sweep only. Then, the control of the

seps2 and 3.

REJUVENATING CORK
PLOORS
Porous curk absorbs dirt
rapidly. To avoid frequent
scrubbing use only the highest
quality pasts wax. When foors
become too solled and abused:
Apply was trip,
minutes.
Then agitate with floor machine and steel twool or synthesis pad. Remove..rinse
thoroughly. allow to dry.
3. Apply a thin roast of clear
paste wax.

3. Apply a thin coat of clear paste wax.
4. Buff with an electric floor polisher. Repeat steps 3 and 4 fi higher gloss is desired.
Note: If cork is extremely worn, faded or discolored, Indian sand will restore color as it waxes. Buff thoroughly.

NEW FLOOR CARE
Newly-installed terrazzo is
normally sealed by the conractor. This is a lifetime seal
in most cases. When installation is complete:

1. Sweep surface dirt and dust.

2. Apply floor cleaner solution
over entire area.

3. Rinse thoroughly...allow
floor to dry.

NEW FLOOR CARE

TERRAZZO

The use of terrazzo

Apply self-polishing wax. Buff thoroughly with an electric polisher if higher gloss is desired.

> offers you... FREE PLANNING on all work! FAMILY ROOMS

REC ROOMS SIDING

ROOFING OFFICE BLDGS. & STORE FRONTS

Shott's Construction Co.

CARPET CLEANING CO. A Breakthrough in Carpet Cleaning RESIDENTIAL . COMMERCIAL . INDUSTRIAL

"CARPETS GLEAM WHEN CLEANED BY STEAM"

20% OFF April 1 thru May 15 FOR FREE ESTIMATES $_{call} 357 - 5830$

CALL DON

427-3247

LICENSED and BONDED



BRYANT WALKER presents...

and/comes alive in tough durable nylon

High Tavon

(Here's a raused (arpet that's been styled for almost any room in your home. Tough and durable, it will add excitement and color to any deron. And at a price like this, you can't afford to let this one escape.

WAREHOUSE

33468 FORD ROAD

Between Wayne and Venoy

OPEN DAILY 9-9 WED. 9-6 CLOSED SUNDAY

PHONE

427-6150 or 427-9730



YOUR HOME IMPROVEMENT HEADQUARTERS





TOWN 'N' COUNTRY HARDWARE 27740 FORD ROAD OPEN DAILY 98 GARDEN CITY



50%