

# SPRING FOR THE BEST!

Now in full color  
Newest Varieties  
of  
**PANSIES & PRIMROSES**



Landscape Designers and Growers of Fine Annual Flowers  
559 Orchard Lake Road, Pontiac, Mi. 48130  
(1 mile E. of Telegraph) Mon.-Sat. 9-5pm, Sun. 10-4pm.

# Redwood knockdown chair

Redwood knockdown deck chair is simple to build

Put it together one way to relax in it, then pull it apart and turn it the other way for space saving storage. This ingenious knockdown redwood deck chair is easy to build using clear all heart redwood. The rewards when the project is completed are a comfortable seat that's easy to store and that won't be ruined if it's left out in the weather.

### Materials needed are:

	amt.	size	length
back legs	2	2x8	40 inches
seat legs	2	2x8	36 inches
seat, back slats	14	3/4x2	20 inches
top handle slat	1	3/4x4	20 inches
support slats	2	3/4x2	17 1/2 inches

flathead woodscrews and plugs

### To assemble:

1. Make full size template for back and seat legs; cut. Cut all slats to size.
2. Make full size template for top slat; cut. Drill 1/4 inch holes to locate outside edges of handle opening. Cut interior with sabre saw or keyhole saw.

3. Round corners and edges of all slats and legs. Sand.

4. Drill 1/2 inch round counterbore plug holes for screws: (a) 1 1/2 inch in from end for back slats; (b) 3 1/4 inch in from end for seat slats; (c) 1/2 inch in from end for supports. Use 2 screws on top slat, support slats, and from and back seat slats. NOTE: The easiest way to free wood plugs from the board is to pry around them gently with a screwdriver until they pop out. Often plugs are deep enough so they can be sliced to make two plugs from one cut.

5. Locate and screw bottom support slat on face of back legs 11 inch up from bottom. Locate and screw supports and back slats so there is 15 inches between inside of legs.

6. Locate and screw top support slat on back leaving 3 1/4 inch between slats.

7. Locate and screw back slats starting with top handle slat, leaving 1/2 inch between slats.

8. Locate and screw 8 seat slats starting with outermost slat and leaving 1/2 inch between slats. There must be 14 1/2 inch between outside of legs.

9. Install plugs, let glue dry thoroughly. Test for fit of sections; if pieces bind adjust by sanding. Sand plugs and finish.

## We Make The Choice Easier!

One visit to THE WINDOW & DOOR STORE will give you all the information required on Weather Shield wood windows and doors. Make the right choice for your building or remodeling needs.

### Consider these advantages:



1. Conference areas are available to review your plans with our expert personnel.
2. A complete line of showroom samples is on location for inspection and demonstration.
3. A large selection of our most popular sizes and styles are stocked on the premises.



Let THE WINDOW & DOOR STORE be your shopping place for energy efficient, quality crafted wood windows and steel doors.



4. Take your selection with you the same day and eliminate lost time waiting for delivery.

**THE WINDOW & DOOR STORE**  
830 Plymouth • Plymouth, MI 48170 • 313-455-8311

## AT THESIER EQUIPMENT

Make your best deal on a John Deere Tractor or Rider.  
Then take another \$25 to \$150 right off the top

Make your best deal on a John Deere rider or tractor today, then take another \$25 to \$150 off the selling price. Choose from 8- and 11-hp riders, 9- to 17-hp lawn tractors, and 10- to 20-hp lawn and garden tractors. We're dealing right now. See us before May 31 and save even more.



Deere Season is on!



Member of the John Deere "Millionaires Club"

Pick up and delivery service Used Equipment


"We Service Well The Things We Sell!"



Use your John Deere Credit Card

90 days same as cash\*

\*No minimum monthly payment, no finance charge during first 90 days. 18% APR, 50-cent minimum monthly finance charge after 90 days.



**THESIER EQUIPMENT CO.**

28342 Pontiac Trail  
South Lyon, MI 48178  
1 mile South of Kensington Metropark  
Livingston County Residents 229-6584 437-2091