


**DON'T GET CAUGHT
IN THE
DARK WITHOUT
ANY HEAT OR WATER**

Generator Sale

54 Series



AG-TRONIC

300 MAX WATTS • 120 VOLT
2500 Continuous

Reg. \$475** SALE **\$375⁰⁰**
Carrying Rack • GAS Engine • 3 hp • Vibration Mounts

5000 MAX WATTS • 120-140 VOLT
4000 Continuous

Reg. \$595** SALE **\$475⁰⁰**
Carrying Rack • GAS Engine • 8 hp • 4 Receptacles •
Vibration Mounts
Electric start model available \$575.00

6250 MAX WATTS • 120-140 VOLT
5000 Continuous

Reg. \$795** SALE **\$575⁰⁰**
Carrying Rack • GAS Engine • 11 hp • 4 Receptacles •
Vibration Mounts
Electric start model available \$695.00

Limited Quantities

New Hudson Power

HOURS: Mon.-Fri. 9-6, Sat. 9-3
53535 Grand River at Hass
CASH CARRY 437-1444



Build a spice rack

Most spice racks on the market are designed to hold a perfectly matched set of jars with neat little labels. Very few good cooks confine themselves to such narrow limits when it comes to spices. So, inevitably, the salt box, the bouillon cubes, the Worcester sauce and many other items still have to be stored on the cupboard shelf.

This redwood spice rack features shelves that are wide enough to accommodate a large variety of cooking supplies. Easy to build from redwood, it will receive the cook's praises for years to come.

Materials needed are: Quantity Size
Length Sides 2 3/4 x 4 28 3/4" Shelves 5
3/4 x 4 23 1/2" Retainer slats 1 3/4 x 4
24" Mounting bar 1 3/4 x 4 24" Finish
nails

To assemble:

1. Cut sides and shelves to size.
2. Cut dados for shelves 3/8" deep and equal to thickness of shelves, leaving 2 1/2" above top shelf and 1/2" below bottom shelf. Leave 6" between the lower shelves and 5" between the two upper shelves (see diagram).
3. Cut notches equal to thickness of retainer slat and 1/2" deep on face of

sides for retainer slats. Leave approximately 1" between top of shelves and bottom of slats.

4. Cut notches equal to thickness of mounting bar, 1 1/2" wide, on back of sides directly below shelf dado.

5. Round by sanding or routing with 1/4" bit: Face corners, inside edges (face, top, and bottom) - Sand inside and routed edges.

6. Attach shelves to sides, being sure assembly is square. Rick uses only glue and clamps but finish nails or screws and plugging can be used as alternatives.

7. Rip 5 slats 1/2" wide from retainer slat piece.

8. Measure for correct length of retainer slats and mounting bar at this time. Leave slats about 1/8" oversize; the ends can be sanded flush after assembly. Use glue and finish nails to attach retainer slats. Set nails, fill and sand.

9. Sand slat ends, flush and round faces of slats and shelves, as well as outside edges of face, top and bottom.

10. Install mounting bar in notches below top shelf, flush with back.

11. Sand and finish.

Spring Cleanup Sale
8 hp Rider

Reg. Value \$1495
Sale **\$795⁰⁰**

Model RMX8

"No hand shifting" variable drive

• Briggs & Stratton engine • CD ignition • All steel construction • Finger tip deck height 1 1/2"-4" • Oversized high rotation tires • Optional gear bagger available.

HOMELITE JACOBSEN

String Trimmer
ST260
Reg. Value \$275**
Sale **\$114⁹⁵**

• 26.2 cc Homelite engine
• Easy line advance
• 17" cutting swath
• Dual setting

VI Super 2-14" Vibration Isolation
• 14" sprocket tip bar • 1.9 cu. in. eng.
• Chrome chain • All metal conal.
• Auto-oil • Weighs 11.5 lbs.
• C.D. Ignition
Reg. Value \$289**
Sale **\$139⁹⁵**

New Hudson Power
53535 Grand River at Hass 2 miles west of Wixom Rd.
HOURS: Mon.-Fri. 9-6; Sat. 9-3 (313) 437-1444
Cash and Carry

Custom Built Green Houses

All Types of Glass Enclosures
Sky-lights • Entry Ways • Slopes

Give your home that **ADDED IMPRESSION**
"The Sky's The Limit"

ADDED IMPRESSION
710 Colebrook • Troy
528-1040
In Home Designer Free Estimates